

XSP-100 SHARK®
Integrated Access Platform
User's Guide

1. GENERAL

- 1.01** This addendum to Publication 9SA-USRS-9.0.2, January 2005, provides updated information related to Software Release 9.02.

2. SOFTWARE VERSION

- 2.01** The Software Version loaded in the Router Module is 9.0.2.

3. CHANGE

- 3.01** This version has no impact on the functional capabilities of the Shark™ IAD. A modification has been made to allow the Router Module to re-start without interrupting any voice connections.

- 3.02** The Transmission Control Port (TCP) number for connecting to the built in web page has been changed from 80 to 8080. This TCP port number change is made to protect the router from anonymous denial of service port attacks. To now access the Graphical User Interface (GUI) provisioning screen, the TCP port number must be specified when entering the Internet Protocol (IP) address in the web browser application. For both Netscape and Microsoft Internet Explorer this is done by appending to the IP address of the Shark™ IAD a colon (:) and the port number of 8080. For example, to access the Shark™ IAD with an IP address of 192.168.1.254 with a TCP port number of 8080, the user must enter <http://192.168.1.254:8080/> in the Uniform Resource Locator (URL) line or Address line.

4. DOCUMENTATION

- 4.01** Use the User's Guide publication number 9SA-USRS-9.0.2 and Getting Started publication number 9SA-STRT-9.0R1.03 for this software release.